



FREESTANDING LABORATORY FREEZER SOLID DOOR 232L WHITE



SKU CODE:	PRODUCT CODE:	DESCRIPTION:
444440970	LSF232UK	Freestanding Laboratory Freezer Solid Door 232L White



-18°C to -25°C Operating Temperature Range
Desired temperature can be set by user

NEW Advanced Controller

Records temperature accurate to 0.1°C

NEW Unique Anti Microbial Handle

Helps prevent the growth of bacteria and minimise the potential for cross contamination

Fitted Lock as Standard

Maintains security and ensures the unit can only be accessed by approved personnel

Fitted Rollers

For ease of movement

Plastic Drawers and Flaps

Maximises space and offers protection to contents

Audible Warning Alarms

Alerts user should internal temperature deviate from set parameters



FULL SPECIFICATION - LSF232UK FREESTANDING LABORATORY FREEZER
SOLID DOOR 232L WHITE

Description	Freestanding
SKU Code	444440970
EAN Code	5052263009707
GDPA Code	LSF232UK
Gross Capacity (L)	232
Net Capacity (L)	212
Unit External Width (mm)	595
Unit External Depth (mm)	634
Unit External Height (mm)	1570
Product Weight (kg)	60
Packed Width (mm)	657
Packed Depth (mm)	734
Packed Height (mm)	1585
Packed Weight (kg)	65
Country of Origin	UK
Internal Dimensions (mm) (WxDxH)	432 x 430 x 1300 (step: 190d x 255h)
External Finish	White
Internal Finish	White
Type of Plastic	SRL800 (HIPS/ABS Mix)
Temperature Range	-18°C to -25°C
Colour	White/Green
Door Type	Solid
Door Style	Hinged, Reversible
Door Open Depth (mm)	1185
Replacement Door Seal	No
Open Door Sensor	Yes
Lock	Yes
Adjustable Feet	2 Adjustable Feet, 2 Rear Rollers
Temperature Display on Panel	Yes
Temperature Alarm	Yes
Number of Shelves	4 Drawers, 2 Fixed Flaps
Number of Shelf Positions	Fixed
Shelf Size	-
Shelf Material	Wire Baskets
Moulded Drawers	4 Solid
Adjustable Door Bins	0
Interior Light	No
Fan	No
Spark Free	Yes
Auto or Manual defrost	Manual
Controller Type	Digital, External
Climate Class	SN
Refrigerant Type	R600a
CFC Free	Yes
HFC Free	Yes
HCFC Free	Yes
UK 3 Pin Plug	Yes
Other Plug Types Available	Yes
Voltage Supply	230
Aux Output	Yes
Insulation Thickness (mm)	60
Insulation Type	Cyclopentane
Anti Microbial Handle	Yes