



Science Equip

Better Products For Laboratory & Industry



www.science-equip.co.uk

## UNDER-COUNTER LABORATORY FREEZER SOLID DOOR 151L WHITE



SKU CODE:	PRODUCT CODE:	DESCRIPTION:
444442773	LSF151UK ATEX	Under-counter Laboratory Freezer Solid Door 151L White



ATEX Approval Zone 2, Category 3



### -18°C to -25°C Operating Temperature Range

Desired temperature can be set by the user

### NEW Advanced Controller

Records temperature accurate to 0.1°C

### NEW Unique Anti Microbial Handle

Helps prevent the growth of bacteria and minimise the potential for cross contamination

### Fitted Lock as Standard

Maintains security and ensures the unit can only be accessed by approved personnel

### Fitted Rollers

For ease of movement

### Wire Baskets

Enables optimum air flow inside unit

### Audible Warning Alarms

Alerts user should internal temperature deviate from set parameters

### ATEX Approved

**FULL SPECIFICATION - ATEX APPROVED LSF151UK UNDER-COUNTER  
LABORATORY FREEZER SOLID DOOR 151L WHITE**

<b>Description</b>	Under-counter
<b>SKU Code</b>	444442773
<b>GDPA Code</b>	LSF151UK ATEX
<b>Gross Capacity (L)</b>	151
<b>Net Capacity (L)</b>	134
<b>Unit External Width (mm)</b>	595
<b>Unit External Depth (mm)</b>	595
<b>Unit External Height (mm)</b>	845
<b>Product Weight (kg)</b>	36
<b>Packed Width (mm)</b>	657
<b>Packed Depth (mm)</b>	694
<b>Packed Height (mm)</b>	884
<b>Packed Weight (kg)</b>	40
<b>Country of Origin</b>	UK
<b>Internal Dimensions (mm) (WxDxH)</b>	500 x 450 x 705 (step: 165d x 185h)
<b>External Finish</b>	White
<b>Internal Finish</b>	White
<b>Type of Plastic</b>	SRL800 (HIPS/ABS Mix)
<b>Temperature Range</b>	-18°C to -25°C
<b>Colour</b>	White/Green
<b>Door Type</b>	Solid
<b>Door Style</b>	Hinged, Reversible
<b>Door Open Depth (mm)</b>	1165
<b>Replacement Door Seal</b>	No
<b>Open Door Sensor</b>	Yes
<b>Lock</b>	Yes
<b>Adjustable Feet</b>	2 Adjustable Feet, 2 Rear Rollers
<b>Temperature Display on Panel</b>	Yes
<b>Temperature Alarm</b>	Yes
<b>Number of Shelves</b>	3 Baskets
<b>Number of Shelf Positions</b>	Fixed
<b>Shelf Size</b>	-
<b>Shelf Material</b>	Wire Baskets
<b>Moulded Drawers</b>	0
<b>Adjustable Door Bins</b>	0
<b>Interior Light</b>	No
<b>Fan</b>	No
<b>Spark Free</b>	Yes
<b>Auto or Manual defrost</b>	Manual
<b>Controller Type</b>	Digital, External
<b>Climate Class</b>	SN
<b>Refrigerant Type</b>	R600a
<b>CFC Free</b>	Yes
<b>HFC Free</b>	Yes
<b>HCFC Free</b>	Yes
<b>UK 3 Pin Plug</b>	Yes
<b>Other Plug Types Available</b>	Yes
<b>Voltage Supply</b>	230
<b>Aux Output</b>	Yes
<b>Insulation Thickness (mm)</b>	45
<b>Insulation Type</b>	Cyclopentane
<b>Anti Microbial Handle</b>	Yes
<b>ATEX Warning</b>	Static Hazard - Clean only with a damp cloth