

C2015 Microtube Centrifuge



Speed500-15000 Rpm
(10 Rpm steps)

Rcf max22,000 G

Timer0-99 Mins & hold
(30 sec steps)

Dims HWD235 x 235 x 350mm

Weight12.8 Kg (without rotor)

Power172 watts

Memory10 programs

Accel rates ...10 programs

Decel rates ...10 programs

Microtube Rotors 15,000 Rpm

NEW

High dome sealed
Polycarbonate lid
included



Rotors

	BRK5424	BRK5436	BRK5448	BRK5494
Rotor type	24 x 2ml	36 x 0.5ml	48 x 0.2ml	4 x Pcr strips
Tube size max	11 x 50mm	8 x 30mm	6 x 40mm	8 per strip
Minimum speed	500 Rpm	500 Rpm	500 Rpm	500 Rpm
Maximum speed	15,000 Rpm	15,000 Rpm	15,000 Rpm	15,000 Rpm
Maximum Rcf (G)	22000	22000	22000	22000
Radius max cms	8.75cms	8.75cms	8.75cms	8.75cms
Sample tube angle (o)	45	45	45	45
Acceleration time (secs)	20	20	20	20
Deceleration time (secs)	20	20	20	20
Autoclaveable (frequency)	121°C (20)	121°C (20)	121°C (20)	121°C (20)

Reducers

Rotor

	BRK5424
Part number Pack 24	RS04 (0.2 - 0.4ml)
Tube size max	6 x 30mm
Part number Pack 24	RS05 (0.5ml)
Tube size max	8 x 30mm

